

Stan A. Huber Consultants, Inc.

Health Physics and Radiation Safety Services

200 North Cedar Road - New Lenox, Illinois 60451-1751 - (800) 383-0468 or (815) 485-6161 - FAX (815) 485-4433 - Email sahci@sahci.com - Home Page www.sahci.com

March 2, 2017 (revised 3/3/17 GAH)

Mike Lanenga SET Environmental 450 Sumac Road Wheeling, Illinois 60090

RE: 371 E. Lower Wacker Drive Thorium Monitoring – City of Chicago Department of Water Management

Dear Mr. Lanenga:

Stan A. Huber Consultants, Inc (SAHCI) was hired by your firm to provide radiation monitoring during the excavation and replacement of a 24" water valve at 371 E. Lower Wacker Drive in Chicago, Illinois. The monitoring was performed by Brian Schmidt, SAHCI Health Physics Technician, on February 28, 2017. All activities were conducted under the guidance of document *SET General Procedure for Thorium Monitoring*.

Instrumentation

Surface gamma scans were performed using a Ludlum Model 2221 Scaled / Ratemeter (serial no. 126496) with attached 2"x2" Nal probe (6" lead shielded). The instrument was calibrated on October 14, 2016. The USEPA action level of 7.1 picocuries per gram (pCi/g) total thorium for this instrument is 7,029 counts per minute (cpm).

The average background count rate for this location was found to average 1,847 cpm.

Soil Gamma Scans

Gamma surface scans were performed using the Ludlum Model 2221 Scaler / Ratemeter described above. Survey data was collected by entering the excavation after each 18 inch lift and recording the highest count rate for the floors and walls to an excavation depth of 3 feet. Soil excavated beyond 3 feet deep was monitored in the excavator bucket as it was removed to a maximum depth of 11.5 feet. All soil was loaded directly into a truck for disposal.

The maximum gamma count rate for each lift was recorded on the attached Radiation Survey Form. The count rates in the excavation ranged from 1,600 cpm to 2,600 cpm. No count rates were found at any time that exceeded the threshold limit of 7,029 cpm.

Additional Monitoring

Since no count rates were identified above the 7.1 pCi/gram threshold limit, no additional soil sampling, air monitoring, or personnel monitoring were performed.

I will be providing a copy of this report to both the City of Chicago Department of Public Health and US Environmental Protection Agency, as required.

Thank you for your assistance with this project. If you have any questions or need additional information, please call me at (815) 485-6161.

Sincerely,

Stan A. Huber Consultants, Inc.

Glenn Huber, CHP

President

	1	_	ı	
Page		 of	_	_



Radiation Survey Form

Location/ Project ID: Pept. WALL MAN	INCENTINT - WATER VALUE PECCENTISSION - VISTA TOWER - LOWER WALLER DR.				
Date: 2/28/17	Technician: MIAN CHAIDT CUKAGO, I				
Inst Model: Lunium - 2221	Serial No. : 126 496				
Probe Type: 1"x1" Nal / 2 x2" Na) Shielded / Not Shielded	Lift Elevation: O - 132"				
Background $\frac{\cancel{\cancel{9}47}}{\cancel{\text{cpm}}}$	Action Level: 7029 cpm				
Write grid designations in circles. Record highes at grid intersections (if required). Shade areas of	st counts for grid in cpm. Record 30 second counts Televated counts and record max cpm.				
	scale				
63'	Lover Prive				
Wayna - VISTA TOWER PROPERTY LIME	B-1 STREET CURB				
D DEPTH S	SPON B-1= 1847 BAGUGROUND (MIN) GOUNT				
48-66" - 2	300				
84-102" -	1800 1800				