

Stan A. Huber Consultants, Inc.

Health Physics and Radiation Safety Services

200 North Cedar Road - New Lenox, Illinois 60451-1751 - (800) 383-0468 or (815) 485-6161 - FAX (815) 485-4433 - Email sahci@sahci.com - Home Page www.sahci.com

November 24, 2020

Mike Lanenga SET Environmental 450 Sumac Road Wheeling, Illinois 60090

RE: Thorium Monitoring – City of Chicago Department of Water Management

CDOT Permit: 1388769 – 535 N. Michigan Ave.

Dear Mr. Lanenga:

Stan A. Huber Consultants, Inc (SAHCI) was hired by your firm to provide radiation monitoring during the excavation for repair of a manhole at 535 N. Michigan Avenue in Chicago, Illinois. The monitoring was performed by Brian Schmidt, SAHCI Health Physics Technician, on November 18, 2020. All activities were conducted under the guidance of document *SET General Procedure for Thorium Monitoring*.

<u>Instrumentation</u>

Surface gamma scans were performed using a Ludlum Model 2221 Scaler / Ratemeter (serial no. 132844) with attached Ludlum Model 44-10 2"x2" Nal Detector (w/ 6" collimated lead shield). The instrument was calibrated on July 28, 2020. The US Environmental Protection Agency (USEPA) action level of 7.1 picocuries per gram (pCi/g) total thorium for this instrument is 7,592 counts per minute (cpm).

The average background count rate for these locations was measured at 1,757 cpm.

Soil Gamma Scans

Gamma surface scans were performed using the Ludlum Model 2221 Scaler / Ratemeter described above. Survey data was collected by entering the excavation surrounding the manhole and recording the highest count rate for the floor and walls to a maximum depth of 30 inches below ground surface. All asphalt, concrete, and soil were loaded directly into a truck for disposal.

The maximum gamma count rate for each lift was recorded on the attached Radiation Survey Form. The count rates in the excavations ranged from 2,000 cpm to 2,400 cpm. No count rates were found at any time that exceeded the threshold limit of 7,592 cpm.

Additional Monitoring

Since no count rates were identified above the 7.1 pCi/gram threshold limit, no additional soil sampling, air monitoring, or personnel monitoring were performed.

I will be providing a copy of this report to both the City of Chicago Department of Public Health and US Environmental Protection Agency, as required.

Thank you for your assistance with this project. If you have any questions or need additional information, please call me at (815) 485-6161.

Sincerely, Stan A. Huber Consultants, Inc.

Glenn Huber, CHP President

	1 .	
Page	of_	



Radiation Survey Form

Location/ Project ID: DWM - 535	N. MICHIGAN AVE MANHOLE REPLACEMENT - KOW KADIOLOGICA
Date: 11/18/2020	N. MICHIGAN ANE MANHOLE REPLACEMENT - KOW KADIOLOGICA SOIL SURVEY Technician: BAIAN SCHMIOT
Inst Model: (UDLUM - 222)	Serial No. : 132 844
Probe Type: 1"x1" Nal 2"x2" Nal Shielded / Not Shielded	Lift Elevation: <u>O-30"</u>
Background 1757 cpm	Action Level: 7592 cpm
Write grid designations in circles. Record high at grid intersections (if required). Shade areas	est counts for grid in cpm. Record 30 second counts of elevated counts and record max cpm.
9 9	scale
162 A2E	OUIO ST. 163' STREET CURB
M,C4162	
EX CANATION TO TEPTU 0-12" 12-30" 30-48"	CPM 12000 12100