

## Stan A. Huber Consultants, Inc.

Health Physics and Radiation Safety Services

200 North Cedar Road - New Lenox, Illinois 60451-1751 - (800) 383-0468 or (815) 485-6161 - FAX (815) 485-4433 - Email sahci@sahci.com - Home Page www.sahci.com

August 16, 2021

Angel Camacho SET Environmental 450 Sumac Road Wheeling, Illinois 60090

RE: Thorium Monitoring – City of Chicago Department of Transportation (CDOT)

CDOT Permit: 1561807 - 548-654 N. Lake Shore Drive

Dear Mr. Camacho:

Stan A. Huber Consultants, Inc (SAHCI) was hired by your firm to provide radiation monitoring during the excavation for construction of a detached CDOT bump out at 548-654 N. Lake Shore Drive in Chicago, Illinois. The monitoring was performed by Brian Schmidt, SAHCI Health Physics Technician, on August 10, 2021. All activities were conducted under the guidance of document *SET General Procedure for Thorium Monitoring*.

## <u>Instrumentation</u>

Surface gamma scans were performed using a Ludlum Model 2221 Scaler / Ratemeter (serial no. 126497) with attached Ludlum Model 44-10 2"x2" Nal Detector (w/ 6" collimated lead shield). The instrument was calibrated on May 5, 2021. The US Environmental Protection Agency (USEPA) action level of 7.1 picocuries per gram (pCi/g) total thorium for this instrument is 6,383 counts per minute (cpm).

The average background count rate for these locations was measured at 1,770 cpm.

## Soil Gamma Scans

Gamma surface scans were performed in the excavation using the Ludlum Model 2221 Scaler / Ratemeter detailed above. Survey data was collected by entering the excavation and recording the highest count rate for the floor and walls to a maximum excavation depth of 18 inches below ground surface. All asphalt, concrete, and soil were loaded directly into a truck for disposal.

The maximum gamma count rate for each lift was recorded on the attached Radiation Survey Form. The count rates in the excavations ranged from 1,800 cpm to 3,900 cpm. No count rates were found at any time that exceeded the threshold limit of 6,383 cpm.

## **Additional Monitoring**

Since no count rates were identified above the 7.1 pCi/gram threshold limit, no additional soil sampling, air monitoring, or personnel monitoring were performed.

I will be providing a copy of this report to both the City of Chicago Department of Public Health and US Environmental Protection Agency, as required.

Thank you for your assistance with this project. If you have any questions or need additional information, please call me at (815) 485-6161.

Sincerely, Stan A. Huber Consultants, Inc.

Glenn Huber, CHP President



Stan A. Huber Consultants, Inc.  Radiatio	on Survey Form
Location/ Project ID: CP OT - BUMP	OUT INSTALL - LSD +OMPANIO ST - KOW KADIOLOGICALO
Date: 8/10/2021	Technician: Brian Schalot RADIOLOGICAL
Inst Model: Lupum - 2221	Serial No. : 121497
Probe Type: 1"x1" Nal / 2 x2" Nal Shielded / Not Shielded	Lift Elevation: O - (8"
Background 1770 cpm	Action Level: 6383 cpm
Write grid designations in circles. Record highest co at grid intersections (if required). Shade areas of ele	
9 9	scale
ONTALIO ST.	101 8' E
EXCAVARION TO PEPTA CON 0-12" (8.00) 12-90" 390 18-36" 320	
1	