

Stan A. Huber Consultants, Inc.

Health Physics and Radiation Safety Services

200 North Cedar Road - New Lenox, Illinois 60451-1751 - (800) 383-0468 or (815) 485-6161 - FAX (815) 485-4433 - Email sahci@sahci.com - Home Page www.sahci.com

October 2, 2021

Angel Camacho SET Environmental 450 Sumac Road Wheeling, Illinois 60090

RE: Thorium Monitoring – 400-402 E. Lower Wacker Drive (Urban Kayaks)

Private Property Dig Number: 601057768

Dear Mr. Camacho:

Stan A. Huber Consultants, Inc (SAHCI) was hired by your firm to provide radiation monitoring during the excavation of a utility trench for electrical service at 400-402 E. Lower Wacker Dr. The excavation was on an existing transformer pad inside the Chicago Auto Impound Lot. The monitoring was performed by Brian Schmidt, SAHCI Health Physics Technician, on September 21, 2021. All activities were conducted under the guidance of document *SET General Procedure for Thorium Monitoring*.

<u>Instrumentation</u>

Surface gamma scans were performed using a Ludlum Model 2221 Scaler / Ratemeter (serial no. 126497) with attached Ludlum Model 44-10 2"x2" Nal Detector (w/ 6" collimated lead shield). The instrument was calibrated on May 5, 2021. The US Environmental Protection Agency (USEPA) action level of 7.1 picocuries per gram (pCi/g) total thorium for this instrument is 6,383 counts per minute (cpm).

The average background count rate for this location was measured at 1,782 cpm.

Soil Gamma Scans

Gamma surface scans were performed using the Ludlum Model 2221 Scaler / Ratemeter described above. Survey data was collected by entering the excavation and recording the highest count rate for the floor and walls to a maximum excavation depth of 3 feet below ground surface.

The maximum gamma count rate for each lift was recorded on the attached Radiation Survey Form. The count rates in the excavation ranged from 1,600 cpm to 2,100 cpm. No count rates were found at any time that exceeded the threshold limit of 6,383 cpm.

Additional Monitoring

Since no count rates were identified above the 7.1 pCi/gram threshold limit, no additional soil sampling, air monitoring, or personnel monitoring were performed.

I will be providing a copy of this report to both the City of Chicago Department of Public Health and US Environmental Protection Agency, as required.

Thank you for your assistance with this project. If you have any questions or need additional information, please call me at (815) 485-6161.

Sincerely, Stan A. Huber Consultants, Inc.

Glenn Huber, CHP President

| Page | _/_ | of | 1 |
|------|-----|----|---|
| | | | |



| Radiatio | on Survey Form |
|---|---|
| Location/ Project ID: JaTAEN - UNS | IN KAMM ELECTRICAL SORVICE WSTALL - ROW RADIOLOGICAL SOIL SURVEY |
| Date: 9/14/2021 | Technician: Brian Schmion |
| Inst Model: Lupeun - 2221 | Serial No.: /26497 |
| Probe Type: 1"x1" Nai / 2"x2" Nal Shielded V Not Shielded | Lift Elevation: 0-36" |
| Background /782 cpm | Action Level: 6383 cpm |
| Write grid designations in circles. Record highest coat grid intersections (if required). Shade areas of ele- | ounts for grid in cpm. Record 30 second counts wated counts and record max cpm. |
| BUSTING TRANSTORMEN PAO AREA | scale |
| 6 Tallow Park | 3', |
| | D "' vs' |
| | |
| | 100' |
| | MOPERTY PERE LINE |
| EXCAVATION TO DEPTH COM 10-18' 1600 18-36" 2100 | |
| 36-54" 1900 | × |