

Stan A. Huber Consultants, Inc.

Health Physics and Radiation Safety Services

200 North Cedar Road - New Lenox, Illinois 60451-1751 - (800) 383-0468 or (815) 485-6161 - FAX (815) 485-4433 - Email sahci@sahci.com - Home Page www.sahci.com

November 22, 2021

Angel Camacho SET Environmental 450 Sumac Road Wheeling, Illinois 60090

RE: Thorium Monitoring – City of Chicago Department of Water Management

CDOT Permit: 1615671 - 324 E. Grand Ave.

Dear Mr. Camacho:

Stan A. Huber Consultants, Inc (SAHCI) was hired by your firm to provide radiation monitoring during the excavation for repair of a Chicago Department of Water Management catch basin outlet at 324 E. Grand Ave. in Chicago, Illinois. The monitoring was performed by Brian Schmidt, SAHCI Health Physics Technician, on November 15, 2021. All activities were conducted under the guidance of document *SET General Procedure for Thorium Monitoring*.

<u>Instrumentation</u>

Surface gamma scans were performed using a Ludlum Model 2221 Scaler / Ratemeter (serial no. 134542) with attached Ludlum Model 44-10 2"x2" Nal Detector (w/ 6" collimated lead shield). The instrument was calibrated on May 5, 2021. The US Environmental Protection Agency (USEPA) action level of 7.1 picocuries per gram (pCi/g) total thorium for this instrument is 7,396 counts per minute (cpm).

The average background count rate for these locations was measured at 1,866 cpm.

Soil Gamma Scans

Gamma surface scans were performed using the Ludlum Model 2221 Scaler / Ratemeter described above. Survey data was collected by entering the excavation and recording the highest count rate for the floor and walls to a depth of 42 inches below ground surface. Material excavated below 42 inches to a maximum depth of 96 inches was screened in the excavator bucket as it was removed. All asphalt, concrete, and soil were loaded directly into a truck for disposal.

The maximum gamma count rate for each lift was recorded on the attached Radiation Survey Form. The count rates in the excavation ranged from 2,500 cpm to 4,300 cpm. No count rates were found at any time that exceeded the threshold limit of 7,396 cpm.

Additional Monitoring

Since no count rates were identified above the 7.1 pCi/gram threshold limit, no additional soil sampling, air monitoring, or personnel monitoring were performed.

I will be providing a copy of this report to both the City of Chicago Department of Public Health and US Environmental Protection Agency, as required.

Thank you for your assistance with this project. If you have any questions or need additional information, please call me at (815) 485-6161.

Sincerely, Stan A. Huber Consultants, Inc.

Glenn Huber, CHP President

	1		1
Page		of	



Radiation Survey Form Location/ Project ID: DWM - SEWER LINE REPAIR -GRAND AVE - ROW RADIOLOGKAL SOIL SURVEY Technician: BRIAN Schnior Date: 11/15/2021 Inst Model: Wown - 2221 Lift Elevation: 0-96 7,396
Action Level: 6758 GAH cpm Probe Type: 1"x1" Nal / ("x2" Nal Shielded / Not Shielded Background 1866 Write grid designations in circles. Record highest counts for grid in cpm. Record 30 second counts at grid intersections (if required). Shade areas of elevated counts and record max cpm. scale GRAND AVE EXCAUSTION ID