

## WEST LAKE LANDFILL SUPERFUND SITE BRIDGETON, MO

#### EXTENT AND DISTRIBUTION OF RIM

December 2017



#### West Lake Landfill Site Vicinity





2

NW St. Louis County

#### North of I-70, and west of I-270



## West Lake Landfill Site Location



- Two near-by residential areas
  - Terrisan Reste Mobile Home Park
  - Spanish Village
- Heavy Commercial, Industrial
- Earth City Business Park (West)
- Approximately 1.5 miles from the Missouri River
- Located near operational runways of the St. Louis Lambert Field International Airport.



### West Lake Landfill Operations



- 5 inactive landfill areas
- Solid waste transfer operation
- Asphalt plant
- Leachate treatment facility
- Crossroads Industrial Park (Lot 2A2)



### West Lake Landfill Operable Units



OU-1:Contains Radiological Impacted Materials (RIM) Area 1 and Area 2 OU-2: Not RIM impacted Closed Demolition Landfill Inactive Sanitary Landfill The Bridgeton Landfill OU-3: Site Wide Groundwater



### West Lake Landfill OU-1

□ OU-1 includes: Area 1, Area 2, and the Buffer Zone/Lot 2A2

Area 1 and Area 2 - landfill cells that contain:

Municipal solid waste (MSW), industrial waste, and construction/demolition debris, some of which is contaminated with radiological material

#### Buffer Zone/Lot 2A2

Historical erosion of Area 2 contaminated these two adjacent properties

#### Site Contaminants:

- Waste or soil contaminated with radiological materials Uranium, Radium, and Thorium (and daughters) identified as COCs
- Other typical landfill contaminants Trace metals and Volatile Organic Compounds also identified as COCs



- Uranium ore processing at the Mallinckrodt facility in St. Louis - Manhattan Project
- Sulfate precipitation
  - removes radium from ore and a small amount of uranium
  - barium sulfate residues created during this processing step which can be leached to recover uranium



FIG. 3.2.A. Dual-cycle ether extraction process, part 1.



- Leached Barium Sulfate Residues (LBSR)
  - Barium sulfate residues further processed (leached) to recover additional uranium
  - Multiple leaching steps can be performed to maximize uranium recovery
  - LBSR contains uranium decay products including radium and thorium
  - Decay products often not in secular equilibrium
  - Small amounts of uranium remain (approximately 0.05% to 0.1%)



- Uranium Ore Processing Operations
  - Processed at plant in downtown St. Louis
  - Moved to Site near St. Louis Airport/Latty Avenue Sites
  - Sold by the federal government to a private party (Continental Mining) and licensed by the Atomic Energy Commission (AEC)
- Cotter Corporation acquires materials
  - Shipped all residuals from Latty Avenue facility to other reprocessing facilities except 8,700 tons of LBSR



- Approximately 8,700 tons of LBSR mixed with about 34,000 tons of impacted soil at Latty Avenue Site
  - Latty Avenue Site located approximately 4 miles from West Lake
  - LBSR spread over the ground surface
  - LBSR excavated along with approximately 18 inches of soil
  - LBSR/soil mix transported by trucks to West Lake Landfill and stockpiled (July – Oct 1973)
  - Materials in these piles used at landfill for cover or other operations



## Landfill Operations

 Used as fill and cover for normal landfilling operations – daily, intermediate, and final cover

- Radiological materials delivered to the site over several months in 1973
  - Potentially stockpiled
  - Time period landfill operations utilized these materials is uncertain

Materials have been found in soil distributed within landfill wastes due to decomposition of trash, differential settlement, and compaction from additional materials placed in and above locations with RIM



#### Landfill Operations





## Landfill Cell Configuration



\*Highly idealized soil layers. This configuration does not reflect mixing of soil with trash or distortion of soil layers by subsequent compaction and placement of additional fill.



#### Landfill Settlement





## Occurrences of RIM

- Radiologically impacted materials (RIM) have contaminated some of the soil materials, solid waste materials, and demolition debris in Area 1 and Area 2
- These materials that have become contaminated are referred to as RIM
- RIM has been found at varying depths (surface and subsurface)
- RIM has been found in discontinuous volumes or layers (thicknesses from a few inches to several feet)



## Definition of RIM

 Site specific background for Ra-226 and Ra-228 estimated at 2.9 pCi/g

Combined Radium (Ra-226 plus Ra-228)

Greater than 7.9 pCi/g

Combined Thorium (Th-230 plus Th-232)

Greater than 7.9 pCi/g

Combined Uranium (U-234 plus U-235 plus U-238)

Greater than 54.5 pCi/g



#### **Basis of RIM Definition**

RIM contains similar radionuclides to uranium mill tailings

Uranium and Thorium decay series

Uranium Mill Tailings Radiation Control Act (UMTRCA) regulations (40 CFR 192) – Residual Radioactive Material

 UMTRCA regulations specify an unrestricted use radium clean-up goal of 5 pCi/g over background (40 CFR 192.12)



#### **Basis of RIM Definition**

OSWER Directive 9200.4-25

Uranium Mill Tailings typically 300-1,000 pCi/g Ra-226

UMTRCA subsurface standard not appropriate for the Site because subsurface contamination exceeds 15 pCi/g

5 pCi/g Ra-226 standard applies to combined Radium and Thorium to define RIM in the surface and subsurface



## **Basis of RIM Definition**

Additional Considerations for Uranium

- 10 CFR 40 Appendix A Criterion 6(6)
  - Dose based ARAR Compared to ARAR protectiveness criteria of 12 mrem/yr (EPA Rad Q&A – Question 35)
  - Dose assessment and ARAR protectiveness evaluation in progress
  - Preliminary evaluations indicate 50 pCi/g over background will not exceed the benchmark dose and the benchmark dose is less than 12 mrem/yr
- Compared to remediation goals from nearby FUSRAP sites
  - St. Louis Airport Site RG for U-238 50 pCi/g over background
  - St. Louis Downtown Site RG for U-238 50 pCi/g over background in top 6 feet, 150 pCi/g over background below 6 feet
- Site-specific risks evaluated in Baseline Risk Assessment

#### **RIM Characterization**



NRC 1970s-1980s (41 Borings)

20

Original EPA RI 1990s (84 Borings)

Phase 1 Investigations 2013-2015 (36 Borings, 112 gamma cone penetration tests)

Additional Characterization 2015 (41 Borings)

Total of approximately 314 Borings and GCPT



## **Summary Data**

#### □ NRC survey (1982)

- 41 Borings, 12 surface samples, plus On-Site testing
- RIM estimated as deep as 455 feet above mean sea level (AMSL) and 20 feet below the ground surface (BGS)
- Estimate of RIM thickness ranged from 2-15 feet in borings
- Areal Extent 2 acres in Area 1, 14 acres in Area 2

#### □ EPA Investigations (1990-2015)

- 273 Borings, Approx. 500 samples
- Sampling shows RIM as deep as 429 feet AMSL and more than 90 feet BGS
- Estimate of RIM thickness is 1-25 feet in borings
- Areal Extent 8.2 acres in Area 1, 24.9 acres in Area 2

#### Sample Locations in Areas 1 and 2



Biased and unbiased sample locations for Areas 1 & 2 are shown.



#### Areal RIM Extent – Area 1





#### Aerial RIM Extent – Area 2





• WL-219 WL-219A

	OU-1 Area Boundary
	Approximate Edge of Refuse
O and 😣	Soil Boring or Surface Soil Sample
*	Location Approximate-No Survey Data Available
	Geostatistical-Based Estimate of RIM Extent
-490	Index Contour
	Intermediate Contour

Depression Contour Building/Structure

Paved Road

LEGEND

- Unpaved Road
- -× Fence

Retaining Wall

Notes:

- The Areal Extent of RIM Shown on this Figure does not Represent a Contiguous Layer, but Rather Portrays the Composite Occurrence of RIM at all Depths/Elevations
- Aerial Topography Provided By Cooper Aerial Surveys Co. and is Dated December 2, 2016
- All Elevations Are Above Mean Sea Level (amsl)

![](_page_24_Picture_0.jpeg)

## **Borings from Additional Characterization**

![](_page_24_Picture_2.jpeg)

![](_page_25_Picture_0.jpeg)

## **Borings from Additional Characterization**

	FEE	ZOR		CORE PHOTOS	340 Solaring S. Jolgan, MCORE 40 Sectors, College, ACM 20 Sectors, College, 5, 1997
Hotelics	Drill Date	<b>Dange</b> e	Recovery	care cinertation	pried interval
AC-10	11022102018		(NAMA)	Tap	(Net below ground suffice)
06 Ber	487.997				
Top-of <u>1.5</u> Ellery	Walds feet LBL347	1	751108		0 - theet
		3	487130		3 - 13 Seid
Bot of 26.3 Elev	Wants Base 408.505	8	52120		19 - 29 Seel

#### AC-1 Boring Log

**RIM Estimated at:** 

4.5'to 22' bgs 29' to 32' bgs 35' to 41' bgs

![](_page_26_Figure_3.jpeg)

![](_page_27_Picture_0.jpeg)

AC-1 Boring Photos

![](_page_27_Picture_2.jpeg)

![](_page_27_Picture_3.jpeg)

AC-20 Boring Log -RIM **Estimated** 19' bgs to 29' bgs

Sam	unle			Borehol	e			Deve	nholi				Core	Core			adium (nCi	oratory Res	ults Th	orium (nCil	1)	Denth
Ru	un In		Geologic Description	(cpm)				Ga	mma				(cpm)	(cpm)	Interval	Ra226	Ra228	Total	Th230	Th232	Total	(ft bgs)
		200	CLAY and GRAVEL (FILL)	945 1163	Ì			Τ			Τ		14484	2								
		Qĭ.		1447					4	L.		1	14970	3	1							lf -
				2125 2025			00 9	900 q	000	000	000	000	15174	2	1							IT .
		QY.		2013 1926			m	3	- Pin	pm -	1	m	14219	2	1							
		111	CLAY, moist, 10YR 6/3 pale brown, silty, with LIMESTONE	1993 2012									14087	2								Γ
		111	tragments (FILL)	1834		E							13928	3								I
		111		1837									14726	2								
	,	111		1819									14693	2								
'		111		1767									15433	3								L
		111.		2101				_	_	_	_	_	15690	1	-							- 10
				1953									16154	1	-							
	_	111		1961		•							15289	2	4							ŀ
		111		2151		:							14308	2	4							ŀ
				2168 2056		ŧ							14344	2	-							ŀ
		<u> (11</u>	CLAY and LIMESTONE fragments as above, moist at base	2156 2040		Ę							13637	2	-							ŀ
1	3	111	(FILL)	2173 2272		Ŧ							14163	2	-							┠
		111		2315 2367		ξ.							12/48	3	-							┠
		111		3336 4109									13114	4	-		Top of	RIM ir	terval			┠
$\vdash$	-	H H	CLAV situ moist minor SAND and SILT / SILL)	7105				<b>*</b>		+			32786	40			<u></u>					- 19
		777	CEAT, sity, most, millor SAND and SILT (PILL)	29853 79441	-			+	+	+	+	-	63634	111	-							- 20
		111	CLAY, stiff, mottled pale brown 10YR 6/3 and dark gray 10YF	383060									128304	197	-							┠
		111		402171 296203									259521	354	-							ŀ
		111		60209									486707	409	23-24'	580	8.43	588	6737 J+	40.44 J+	6777	+
1	4	111		9775			. •		1				192744	133								+
				4593			•						41703	96	1							ŀ
			LANDFILLED MATERIAL, nondescript (WASTE); Top of Waste Elevation = 463.306	3016		1							22858	51	1							IF .
			CLAY sity (WASTE)	3262									18569	41	1							IF .
		O.	LANDER LED MATERIAL producerint (M/ASTE)	2465 2048		F							16567	41								20
				1604									13667	1		B	ottom	of RIM	interva			29
			SAND and CLAY in distinct bands (WASTE)	2147									13113	2		-						_ 30
			LANDFILLED MATERIAL, wood pieces, electrical cord/wire (WASTE)	2378 2164		ŧ.							13003	1								
				1838									12948	3								L
4	5			751	2								13280	2								L
				637 708	\$								13479	4	4							IL .
				1048									13207	3	-							ŀ
				1485		5	600	800	1000	1200	-1400	1600	12993	5	-							ŀ
		20	CLAY and GRAVEL (WASTE)	2008		6	- Ochai	opm	-cpn	d opn	-pn	-cpn	12657	1	-							┠
$\vdash$	_	رور		2001				1	1	1	1	1	12488	2	-							ŀ
			LANDFILLED MATERIAL, metal tubing, blue plastic, rubber hose (WASTE); Bottom of Waste Elevation = 440.976	2034 2472	<u> </u>			+	+	+	+	-	13150	~	-							- 40
				2267 2046		ř.							13103	3	-							┠
				1503 1124	1								13413	2	-							┠
				1022	ž								13323	1	-							┠
	6			803-	Ĭ								13415	4	-							┠
				736									13937	1	1							╟
				1346		•							14843	0	1							ŀ
				3620									15012	3								+
		111	CLAY, stiff, highly plastic in top foot, silly bottom 9 inches	4147 4185									14406	1	47-49'	1.33	1.55	2.88	1.54 J+	1.06 J+	2.60	lt
				-				-	-	-	-			-	-	-	-	-	-	-		- 1

Core

---- Laboratory Results ----

Borehole

![](_page_29_Picture_0.jpeg)

#### AC-20 – Actual Boring Photos

![](_page_29_Picture_2.jpeg)

![](_page_30_Picture_0.jpeg)

### **Geostatistical Evaluation of Data**

- Geostatistical estimates of the volume and extent of RIM were conducted as presented within the FFS – using 3D indicator kriging.
- Estimates also included volumes of non-RIM impacted overburden and "set-back" due to excavation safety concerns.
  - Maximum areal extent of RIM in Area 1 is approximately 8.4 acres.
  - Maximum areal extent of RIM in Area 2 is approximately 26.8 acres
  - Area 1 vol. estimate is 58,700 cubic yards of RIM
  - Area 2 vol. estimate is 251,000 cubic yards of RIM

## SUPERIOR STATES

#### **Volume Considerations**

Area 1 - Total RIM Volume					
Threshold 7.9 pCi/g					
RIM	58,700				
Vertical Over Burden	355,000				
Excavation Setback	472,000				
Total Volume	885,700				

Area 2 - Total RIM Volume						
Threshold 7.9 pCi/g						
RIM	251,000					
Vertical Over Burden	376,000					
Excavation Setback	334,000					
Total Volume	961,000					

![](_page_32_Picture_0.jpeg)

![](_page_32_Picture_1.jpeg)