

83136

O'MARA<sup>4-82</sup>

04

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
OFFICE OF LEGAL AND ENFORCEMENT COUNSEL

EPA-330/2-82-001

SUMMARY OF PINE RIVER RESERVOIR  
SEDIMENT SAMPLING SURVEY

St. Louis, Michigan  
November 20-22, 1981

April 1982

Russell Forba

NATIONAL ENFORCEMENT INVESTIGATIONS CENTER  
Denver, Colorado

## CONTENTS

INTRODUCTION . . . . .	1
CONCLUSIONS . . . . .	1
METHODS . . . . .	3
SURVEY FINDINGS . . . . .	8
PHYSICAL OBSERVATIONS . . . . .	8
ANALYTICAL RESULTS . . . . .	8

## Tables

1 Sediment Sampling Locations . . . . .	4
2 Sediment Core Descriptions . . . . .	6
3 Total DDT, HBB, and PBB Concentrations In Sediments By Basin . .	10
4 Total DDT, HBB, and PBB Concentrations In Sediments By Depths . .	15

## Figures

1 Sediment Sampling Locations . . . . .	2
2 Total DDT Contamination . . . . .	11
3 HBB Contamination . . . . .	12
4 PBB Contamination . . . . .	13

## APPENDICES

A TOTAL DDT, HBB, AND PBB LOADING APPROXIMATIONS	
B COMPLETE ANALYTICAL DATA AND METHODS AND ASSOCIATED QUALITY CONTROL DATA	

## INTRODUCTION

In June 1980\* NEIC collected water and sediment samples from the Pine River to document the contamination contributed to the Pine River by previous operations of the Velsicol Chemical Corporation (VCC) at its St. Louis, Michigan facility.

At the request of Region 5, Enforcement Division, additional sediment sampling was conducted November 20 to 22, 1981 to supplement the June 1980 sampling and to more adequately define the areal and vertical distribution of total DDT, HBB, and PBB in the Pine River Reservoir. This new information was needed to support settlement negotiations between the regulatory agencies and VCC.

## CONCLUSIONS

The NEIC sediment sampling data showed widespread contamination of the Pine River Reservoir by DDT, hexabromobenzene (HBB), and polybrominated biphenyl (PBB). An estimated 56,000 lb DDT, 10,000 lb HBB, and 800 lb PBB are contained in the Pine River Reservoir sediments.


The highest levels of contaminants were found in the middle basin (sampling Stations 04 to 18) of the reservoir located between the VCC Plant Site Jetty and the Mill Street Bridge [Figure 1]. Within this basin, the highest concentration of contaminants was found near the VCC plant site boundary, offshore from the former discharge points for the VCC organics production area. The maximum concentrations of total DDT, HBB, and PBB found in the segments of cores were 26,000 µg/g, 9,300 µg/g, and 330 µg/g, respectively. The lower basin (sampling Stations 19 to 23), located between

---

\* EPA-330/2-8-031 - Pine River Contamination Survey, St. Louis, Michigan - October 1980.

EPA-330/2-8-030 - Investigation for Hazardous Waste Contamination, Velsicol Chemical Corporation Plant Site, St. Louis, Michigan - October 1980.

FIGURE 1  
SEDIMENT SAMPLING LOCATIONS  
PINE RIVER RESERVOIR  
St. Louis, Michigan  
November 20-22, 1981



the Mill Street Bridge and the St. Louis Dam, was found to be contaminated, but to a lesser degree than the middle basin. Maximum concentrations of total DDT, HBB, and PBB found in this area were 560 µg/g, 180 µg/g, and 5.2 µg/g, respectively. In the upper basin (sampling Stations 01, 02, and 03), located upstream of the VCC plant site jetty, the contaminant levels were lower with maximum total DDT, HBB, and PBB concentrations of 25 µg/g, 3.2 µg/g, and 2.8 µg/g, respectively.

Regardless of the areal distribution of the contaminants, the highest DDT levels were found in the deeper portions of the sediment cores with lower concentrations in the top 4 inches. High levels of DDT are also found in surface sediments (4,000 µg/g at Station 14) in areas of the reservoir where scouring had apparently exposed the older sediments. The highest levels of HBB and PBB were found in the top (0 to 16 in.) of the cores. Logically, the HBB and PBB should be more prevalent in the surface sediments, and DDT should be prevalent in the deeper sediments because HBB and PBB were produced until the mid-1970s, while DDT production ceased in 1959.

#### METHODS

Sediment cores were collected and water and sediment depths measured at 23 sampling locations [Figure 1, Table 1]. The sediment depths were measured by penetrating the reservoir bottom with a ½ in. diameter steel rod until resistance was met. Water depth was obtained by dropping a disc (approximately 16 in. diameter) into the reservoir bottom and measuring the submerged portion of the attached cord.

The sediment samples were collected in 1-3/4 in. I.D. hexane-rinsed aluminum or galvanized steel core tubes. To facilitate sampling and handling, core tubes of 3, 4, or 6 ft in length were used. The samples were collected by slowly pushing or driving the core tubes into the sediment until a sediment layer, which was compacted hard enough to plug the end of the core tube, was reached. Care was taken to allow several inches of water to

Table 1  
SEDIMENT SAMPLING LOCATIONS  
PINE RIVER RESERVOIR  
ST. LOUIS, MICHIGAN  
November 20-22, 1981

Core Sampling	Sampling Date & Time (ft)	Depth of Water (ft)	Depth of Sediment (ft)	Core Tube Length	Station Description
01	11/20/81 1315 hrs	8	1.5	3	50 feet from the shoreline adjacent to the Velsicol Chemical Corporation (VCC) plant site, 2100 feet upstream of the VCC jetty.
02	11/20/81 1340 hrs	2	1.5	3	Same as above (01) except 900 feet upstream of the VCC jetty.
03	11/20/81 1420 hrs	4	9	4	Same as above (01) except 300 feet upstream of the VCC jetty.
04	11/20/81 1530 hrs	1	8	4	50 feet from the shoreline adjacent to the VCC plant site on the north-south transect located 1200 feet west of the Mill Street Bridge.
05	11/20/81 1545 hrs	1.5	9	6	Same as above (04) except 150 feet from the VCC shoreline.
06	11/20/81 1600 hrs	5	9	6	Same as above (04) except 300 feet from the VCC shoreline.
07	11/21/81 1125 hrs	4	6	4	50 feet from the shoreline adjacent to the VCC plant site on the north-south transect located 900 feet west of the Mill Street Bridge.
08	11/21/81 1140 hrs	3	3	3	Same as above (07) except 150 feet from the VCC shoreline.
09	11/21/81 1200 hrs	3	4.5	4	Same as above (07) except 300 feet from the VCC shoreline.
10	11/21/81 1215 hrs	3	7	6	Same as above (07) except 500 feet from the VCC shoreline.
11	11/21/81 1230 hrs	5.5	4	4	50 feet from the shoreline adjacent to the VCC plant site on the north-south transect located 600 feet west of the Mill Street Bridge.
12	11/21/81 1245 hrs	5	8	6	Same as above (11) except 150 feet from the VCC shoreline.
13	11/21/81 1300 hrs	4	8	6	Same as above (11) except 300 feet from the VCC shoreline.
14	11/21/81 1335 hrs	4	2	4	Same as above (11) except 500 feet from the VCC shoreline.
15	11/21/81 1430 hrs	7	7	6	50 feet from the shoreline adjacent to the VCC plant site on the north-south transect located 300 feet west of the Mill Street Bridge.
16	11/21/81 1445 hrs	5	8	6	Same as above (15) except 150 feet from the VCC shoreline.
17	11/21/81 1500 hrs	5	8	6	Same as above (15) except 300 feet from the VCC shoreline.
18	11/21/81 1520 hrs	7	3	4	Same as above (15) except 500 feet from the VCC shoreline.
18-dup	11/21/81 1520 hrs	7	3	4	Same as above (18)
19	11/22/81 0930 hrs	8	2	3	150 feet east of the midpoint of the Mill Street Bridge.
20	11/22/81 0945 hrs	8	2	3	300 feet east of the midpoint of the Mill Street Bridge.
21	11/22/81 1000 hrs	7	4	3	450 feet east of the midpoint of the Mill Street Bridge.
21 dup	11/22/81 1000 hrs	7	4	3	Same as above (21)
22	11/22/81 1015 hrs	8	6	3	150 feet north of Station 20.
23	11/22/81 1020 hrs	8	3	3	150 feet north of the midpoint of the City of St. Louis municipal dam.

remain in the top of the core tubes to ensure that there was minimal disturbance of the surface sediment. The filled tubes were extracted from the bottom, the ends were sealed with aluminum foil, and then they were capped and frozen in an upright position.

After freezing, the 4 and 6 ft core tubes were cut in half, the open ends covered with aluminum foil, and stored in dry ice. At the NEIC laboratory, the frozen samples were extruded from the core tubes by warming the outside of the tubes with water and pushing the frozen cores from the tubes. After extrusion, each frozen core was observed and the physical characteristics recorded [Table 2]. The top 4 inches of each sediment sample was separated from the core and the remainder divided, from top to bottom, in 1 ft intervals or fractions of a foot, as applicable. All segments of each sediment core were wrapped in aluminum foil. These segments were subsequently thawed, thoroughly mixed, and analyzed for PBB, total DDT, and HBB. Complete analytical methodology is shown in Attachment A. NEIC chain-of-custody and document control procedures were followed throughout the survey.

Table 2  
SEDIMENT CORE DESCRIPTIONS  
PINE RIVER RESERVOIR  
St. Louis, Michigan  
November 20-22, 1981

Station Number	Extrusion Date and Time	Total Length (in.)	Core Segment (in.)	Visual Description*
01	12/1/81 1200 hrs	13	0-3 3-10 10-13	gray-brown floc grading into gray-brown silt gray-brown silt gray-black sludge
02	11/30/81 1400 hrs	17	0-4 8-14 14-17	brown sandy silt white silt (MgO <sub>2</sub> ) black sludge
03	12/1/81 0955 hrs	24	0-6 6-10 10-24	black sludge gray-white silt (MgO <sub>2</sub> ) white silt (MgO <sub>2</sub> )
04	11/30/81 1425 hrs	13	0-9 9-13	dark gray-brown sandy silt black silt
05	11/30/81 1335 hrs	40	0-4 4-13 13-15 15-40	brown-gray floc grading into gray-brown silt gray-black sludge white silt (MgO <sub>2</sub> ) gray-black sludge
06	11/30/81 1440 hrs	32	0-4 4-13 13-32	gray-brown floc grading into gray-brown sandy silt gray sandy silt gray-white silt
07	11/30/81 1450 hrs	36	0-6 6-20 20-36	brown floc black silty sand gray-black sandy silt
08	11/30/81 1325 hrs	28	0-4 4-28	brown-gray floc grading into brown-gray silt gray-black silt
09	11/30/81 1315 hrs	34	0-34	gray-black silt
10	11/30/81 1500 hrs	24	0-8 8-14 14-24	gray sand with streaks of white silt (MgO) gray sand black sandy silt
11	11/30/81 1310 hrs	16	0-4 4-16	gray-brown floc grading into gray-black silt gray-black silt
12	11/30/81 1520 hrs	30	0-3 3-30	gray-brown floc grading into gray-black silt gray-black silt
13	11/30/81 1300 hrs	46	0-6 6-46	gray-brown floc grading into silty gray-black gray-black silt
14	12/1/81 0830 hrs	28	0-4 4-8 8-28	gray-brown floc grading into gray-black silty sand black silty sand gray-brown coarse sand
15	12/1/81 0915 hrs	46	0-2 2-46	black floc dark black sludge



Table 2 (Cont.)  
 SEDIMENT CORE DESCRIPTIONS  
 PINE RIVER RESERVOIR  
 St. Louis, Michigan  
 November 20-22, 1981

Station Number	Extrusion Date and Time	Total Length (in.)	Core Segment (in.)	Visual Description*
16	11/30/81 1250 hrs	42	0-12 12-42	gray-brown silt black sludge
17	12/1/81 0935 hrs	45	0-4 4-9 9-40 40-45	brown floc black and gray-white silt layers black silt brown-gray clay
18	11/30/81 1220 hrs	35	0-11 11-35	gray-brown floc grading into fine gray-brown silt black silt
18-dup	11/30/81 1240 hrs	34	0-11 11-34	gray-brown floc grading into fine gray brown silt black silt
19	12/1/81 1015 hrs	22	0-3 3-18 18-22	brown-gray floc grading into black silt black sludge fine gray-brown silt
20	11/30/81 1345 hrs	27	0-5 5-19 19-27	gray-black silt black sludge light brown clay
21	12/1/81 1035 hrs	21	0-5 5-13 13-21	brown-gray floc grading into black silt black silt gray-black silt
21 dup	12/1/81 1135 hrs	14	0-4 4-14	brown-gray floc grading into black silt black silt
22	12/1/81 1145 hrs	23	0-6 6-18 18-23	brown-gray floc grading into black silt black silt gray-black silt
23	12/1/81 1200 hrs	34	0-3 3-28 28-34	gray-brown floc black silt gray-brown silty sand

\* Descriptions are from visual observations of the outside of the frozen cores after extrusion from the core tubes.

## SURVEY FINDINGS

### PHYSICAL OBSERVATIONS

Total sediment depth at the sampling Stations varied between 1.5 and 9 ft [Table 1]. The deepest sediments (8 to 9 ft) were found in the extreme upper end (Stations 04, 05, and 06) and lower end (Stations 12, 13, 16, and 17) of the middle basin.

After extrusion of the sediment cores, the physical characteristics of the sediment cores were observed and recorded [Table 2]. Many of the cores (78%) contained a surface layer (1 to 6 inches) of gray-brown floc (light silty filamentous material). Nearly all the cores contained layers of varying thickness of black or gray-black sludge. A sulfurous odor was noticed in the cores which contained this black sludge. The strongest odors were from samples collected at Stations 07, 08, 15, 19, 20, and 23. Many of the cores contained layers of white sludge which, according to Company officials, is probably magnesium oxide (MgO). Both the black and white layers had a very small grain size, usually indiscernible to the naked eye.

The black and white layers of materials seen in the cores varied in thickness and depth; hence, no visual correlation of the layers between sampling stations could be made. These varying depths and thicknesses of sediment layers and the differences in total sediment depths at the sampling stations showed the expected variability in deposition rates within the reservoir.

### ANALYTICAL RESULTS

Approximately 56,000 lbs DDT, 10,000 lbs HBB, and 800 lbs PBB are contained in the Pine River sediments. Less than 5% of the DDT is found in the top 4 in. of sediment, but over 13% of the HBB and 57% of the PBB was found in the top 4 in. of the cores. These loadings were calculated by

(25)

integrating sediment density, contaminant concentration by depth, and the areas assigned to each of the sampling Stations [Appendix A].

The highest concentrations of total DDT, HBB, and PBB [Table 3] were found in the middle basin of the Pine River Reservoir (Stations 04-18) which extends from the VCC plant site jetty to the Mill Street Bridge [Figure 1]. Average maximum total DDT, HBB, and PBB concentrations\* in the samples collected in this basin were 3,500 µg/g, 1,000 µg/g, and 42 µg/g, respectively. Wastewater from the former VCC organics production area was discharged to this portion of the basin. Within this basin, the highest total DDT concentrations were found at Stations 07 (26,000 µg/g) and 08 (8,800 µg/g). The highest concentrations of HBB were also found at Station 07 (9,300 µg/g) and 08 (2,600 µg/g). Highest PBB concentrations were found at Station 04 (330 µg/g), 10 (66 µg/g), 07 (64 µg/g), and 08 (58 µg/g). Stations 07 and 08 are the Stations nearest to the former organics wastewater discharges, and they are close to the location where the highest total DDT concentration (44,000 µg/g) was found during the June 1980 NEIC survey.\*\* Contaminant concentrations within the middle basin generally decreased [Figures 2, 3, and 4] toward the northern shore. The old river channel is located along this shoreline.

Compared to the middle basin, the average concentrations of contaminants in the upper basin are low. Average maximum core concentrations of total DDT, HBB, and PBB of 11 µg/g, 1.8 µg/g, and 1.5 µg/g, respectively, were found in this portion of the reservoir which extends from the Washington Street Bridge to the VCC plant site jetty (Stations 01, 02, and 03).

The lower basin (Stations 19 to 23) of the reservoir between the Mill Street Bridge and the St. Louis Municipal Dam was found to be contaminated; however, contaminant concentrations were lower than the levels found in the middle basin. Average maximum core concentrations of total DDT, HBB, and PBB found in this area were 310 µg/g, 81 µg/g, and 4.2 µg/g, respectively.

\* The average maximum concentrations were calculated by averaging the concentrations of the most contaminated segment of each core.


\*\* EPA-330/2-80-031 - Pine River Contamination Survey, St. Louis, Michigan - October 1980.

Table 3  
TOTAL DDT, HBB, AND PBB CONCENTRATIONS  
IN SEDIMENTS BY BASIN  
PINE RIVER RESERVOIR  
St. Louis, Michigan  
November 20-22, 1981

Basin	Sample Size Stations	Total DDT		HBB		PBB	
		Avg.- Maximum Concentration µg/g	Maximum Concentration µg/g	Avg.- Maximum Concentration µg/g	Maximum Concentration µg/g	Avg.- Maximum Concentration µg/g	Maximum Concentration µg/g
UPPER Stations 01-03	3	11	25	1.8	3.2	1.5	2.8
MIDDLE Stations 04-18	15	3500	26,000	1000	9300	42	330
LOWER Stations 19-23	5	300	560	81	180	4.2	5.2


\* This average maximum concentration was calculated by averaging the concentrations of the most contaminated segment of each core.

FIGURE 2  
TOTAL DDT CONTAMINATION  
PINE RIVER RESERVOIR  
St. Louis, Michigan  
November 20-22, 1981




\* Based on maximum concentrations found in individual sediment cores

FIGURE 3  
HBB CONTAMINATION  
PINE RIVER RESERVOIR  
St. Louis, Michigan  
November 20-22, 1981



\* Based on maximum concentrations found in individual sediment cores

FIGURE 4  
PBB CONTAMINATION  
PINE RIVER RESERVOIR  
St. Louis, Michigan  
November 20-22, 1981



\* Based on maximum concentrations found in individual sediment cores

A concentration profile by depth [Table 4] was developed by summarizing the data from each of 5 specified depths (0 to 4 in., 4 to 16 in., 16 to 28 in., 28 to 40 in., and 40 in. and below) from the 20 sampling Stations in the middle and lower basins (Stations 04 to 23).<sup>\*</sup> This profile showed the highest average total DDT concentrations were found to be in the deeper sediment layers (16 to 28 in. and 28 to 40 in. layers). An average total DDT concentration of 960 µg/g was found in the 16 to 28 in. segments of the sediment cores, and 1,000 µg/g was found in the 18 to 40 in. segments.

Conversely, lower concentrations of total DDT were generally found in the surface portion (0 to 4 in.) of the sediment cores. One station (14), however, had a surface sediment total DDT concentration of 4,000 µg/g. This high concentration is probably due to the deposition and erosion patterns in the reservoir. Station 14 is located at the edge of the main river channel which runs along the north side of the reservoir. The velocity of the currents would be expected to be higher in this area of the reservoir during high flow periods, increasing scouring and exposing the older and deeper layers of sediment which contain higher total DDT levels. The analyses of the three cores which were greater than 40 in. in length showed very low concentrations of contaminants below the 40 in. level.

Maximum HBB and PBB concentrations were generally found to be in the upper sediments (0 to 16 in.). A maximum HBB concentration of 9,300 µg/g was found in the 4 to 16 in. layer at Station 07, and a maximum PBB concentration of 330 µg/g was found in the 0 to 4 in. layer at Station 04.

Complete analytical data for all the sediment samples, as well as the analytical methods and associated quality control data, can be seen in Appendix B.

---

<sup>\*</sup> Sediment cores were divided into two to five segments depending on each core's length.



Table 4  
TOTAL DDT, HBB, AND PBB CONCENTRATIONS<sup>1</sup>  
IN SEDIMENTS BY BASIN  
PINE RIVER RESERVOIR  
St. Louis, Michigan  
November 20-22, 1981

Core Seg. Depth (in.)	Sample Size Stations	Total DDT		HBB		PBB	
		Avg. <sup>2</sup> -Maximum Concentration µg/g	Maximum Concentration µg/g	Avg. <sup>2</sup> -Maximum Concentration µg/g	Maximum Concentration µg/g	Avg. <sup>2</sup> -Maximum Concentration µg/g	Maximum Concentration µg/g
0-4	19	34	4,000	61	2,600	8.6	330
4-16	19	159	2,900	255	9,300	7.4	66
16-28	17	957	26,000	5.8	100	0	1
28-40	9 <sup>3</sup>	1014	4,800	0.13	44	0	0
40-46	3	3.3	9.5	0	0	0	0

1 Dry weight concentrations

2 This average was derived by comparing the mean concentration of the entire set (Stations 04-23) at the various depths with individual values, dismissing values which were more than 2 standard deviations from the mean, and calculating a new average with the remaining values. This average is not the true average but an expected average with depth. The high values dismissed are valid concentrations although not typical for the majority of the cores.

3 A sample size of 8 was used to derive the average concentrations for HBB.

**APPENDIX A**

**TOTAL DDT, HBB, AND PBB LOADING APPROXIMATIONS**



TOTAL DDT, HBB, AND PBB LOADING APPROXIMATIONS\*  
PINE RIVER RESERVOIR  
St. Louis, Michigan

A-1

Sample Number*	% H <sub>2</sub> O	Sediment Density lbs/ft <sup>3</sup>	Area ft <sup>3</sup>	Total DDT Loading lbs	HBB Loading lbs	PBB Loading lbs
01-1	54.3	80.6	-	-	-	-
01-2	63.9	81.0	-	-	-	-
02-1	55.4	87.3	185,760	12.1	2.41	2.41
02-2	48.2	93.6	"	63.0	9.91	6.84
03-1	64.9	80.1	216,000	3.44	1.94	1.70
03-2	64.1	82.9	"	125	-	-
03-3	51.8	90.2	"	235	-	-
04-1	34.8	107.2	54,000	340	18.9	415
04-2	45.2	96.5	"	343	257	65.7
05-1	63.2	81.3	36,000	5.03	33.0	0.34
05-2	65.3	79.9	"	24.0	6.19	-
05-3	68.1	78.1	"	888	-	-
05-4	61.6	82.4	"	-	-	-
06-1	57.1	85.8	54,000	1.71	7.95	1.46
06-2	43.7	98.8	"	10.5	84.1	1.68
06-3	60.5	83.3	"	13.9	1.63	-
06-4	51.9	90.2	"	-	-	-
07-1	72.0	75.8	18,000	12.7	-	1.78
07-2	71.5	76.0	"	148	3626	25.0
07-3	61.3	82.7	"	14980	57.6	-
07-4	63.4	81.2	"	2.51	0.53	-
08-1	70.3	76.7	50,400	13.8	994	22.2
08-2	70.8	76.5	"	3265	2027	-
08-3	63.2	81.3	"	14940	-	-
09-1	65.6	79.8	54,000	16.3	69.2	8.90
09-2	68.3	78.0	"	801	32	24
09-3	59.6	84.0	"	143	-	-
09-4	62.4	81.8	"	9.13	-	-
10-1	68.0	78.2	57,600	2.79	26.4	6.73
10-2	64.1	80.7	"	751	734	110
10-3	56.3	86.6	"	17.0	30.5	-
11-1	68.5	77.9	25,200	3.5	20.0	1.0
11-2	65.6	79.8	"	22.8	422	14.5
12-1	68.7	77.8	32,400	3.94	23.7	1.31
12-2	63.5	81.2	"	15.4	163	7.68
12-3	55.9	86.9	"	-	-	-
13-1	67.1	78.7	61,200	7.92	23.2	2.22
13-2	67.7	78.3	"	24.8	774	38.7
13-3	67.4	78.5	"	345	43.9	1.57
13-4	62.2	82.0	"	9105	-	-
13-5	55.2	87.4	"	18	-	-
14-1	66.5	79.1	64,000	2289	3.26	1.55
14-2	13.5	140.0	"	243	-	-
14-3	15.1	137.0	"	-	-	-
15-1	71.9	75.8	12,960	1.93	7.36	0.37
15-2	68.9	77.7	"	6.58	207	5.01
15-3	67.1	78.7	"	1804	18	-
15-4	58.8	84.5	"	1940	19.9	-

TOTAL DDT, HBB, AND PBB LOADING APPROXIMATIONS\* (Cont)  
PINE RIVER RESERVOIR  
St. Louis, Michigan

Sample Number*	% H <sub>2</sub> O	Sediment Density lbs/ft <sup>3</sup>	Area ft <sup>2</sup>	Total DDT Loading lbs	HBB Loading lbs	PBB Loading lbs
15-5	56.3	86.5	"	.12	-	-
16-1	64.1	80.7	58,464	21.5	48.6	6.78
16-2	64.5	80.5	"	50.1	368	10.9
16-3	67.1	78.7	"	81.7	-	-
16-4	55.0	87.5	"	25.3	-	-
17-1	64.2	80.6	64,800	14.3	32	3.3
17-2	68.0	78.2	"	9.24	195	2.59
17-3	63.7	81.1	"	496	3.62	-
17-4	57.3	85.7	"	.78	-	-
17-5	36.8	105	"	-	-	-
18-1	64.0	80.7	102,600	20.9	4.27	1.19
18-2	31.3	111.7	"	2.83	4.57	-
18-3	61.6	82.4	"	390	-	-
18-4 dup.	66.3	79.2	102,000	12.8	4.56	1.19
18-2 dup.	30.2	113	"	31.6	6.55	55
18-3 dup.	56.9	86.0	"	532	-	-
19-1	56.5	86.4	43,200	5.95	18.4	1.62
19-2	70.5	76.6	"	85.9	41	4.69
19-3	34.8	107.2	"	-	-	-
20-1	61.8	82.3	37,440	0.51	32.2	1.33
20-2	68.6	77.8	"	512	25.6	-
20-3	18.4	131.0	"	4.4	-	-
21-1	66.6	79.1	48,960	4.05	23.2	1.47
21-2	69.4	77.4	"	232	37.1	-
21-3	51.9	90.1	"	-	-	-
21-1 dup.	67.9	78.2	48,960	3.69	21.3	1.35
21-2 dup.	70.0	76.9	"	181	44.1	-
22-1	70.3	76.7	90,514	5.91	24.1	1.44
22-2	72.3	75.7	"	702	91.1	9.87
22-3	64.9	80.1	"	40.7	-	-
23-1	66.6	79.1	50,914	345	80.7	1.97
23-2	67.6	78.4	"	113	28.5	-
23-3	67.1	78.7	"	409	-	-
23-4	46.6	95.1	"	-	-	-
Total				56,286	10,808	843
0 to 4 in.				2,787	1,494	486
4 to 16 in.				7,940	9,138	355
16 to 18 in.				34,859	155	2
28 to 40 in.				11,083	20	0
40 in. and over				18	0	0

\* Based on NEIC data from samples collected November 20 to 22, 1981.

\*\* The first two digits refer to the sampling station number. The last digit refers to the depth of each sediment core portion as follows: 1 = 0 to 4 in., 2 = 4 to 16 in., 3 = 16 to 28 in., 4 = 28 to 40 in., 5 = 40 in. and over.

**APPENDIX B**

**COMPLETE ANALYTICAL DATA AND METHODS  
AND ASSOCIATED QUALITY CONTROL DATA**

ENVIRONMENTAL PROTECTION AGENCY  
OFFICE OF ENFORCEMENT  
NATIONAL ENFORCEMENT INVESTIGATIONS CENTER  
BUILDING 53, BOX 25227, DENVER FEDERAL CENTER  
DENVER, COLORADO 80225

B-1

TO : Russell Forba, Project Coordinator

DATE: January 14, 1982

FROM : Charles P. Rzeszutko, Chemist  
THRU: Dean F. Hill, Chief  
Pesticide and Toxic Substances Branch  
SUBJECT: Project #624, Pine River, St. Louis, MI

Attached you will find the results of analysis for all core samples received for Project #624. All cores were analyzed for DDT and related compounds, hexabromobenzene (HBB), and polybrominated biphenyls (PBB). Methodology and quality control data are provided. Results previously reported on December 16, 1981, are included in this report.

If you have any questions, please contact me at your convenience.

cc: R. Laidlaw  
T. Meiggs  
Attachments

## BACKGROUND

On November 30, 1981, 23 core samples were received for analysis by the Pesticide and Toxic Substances Branch as part of the Pine River Reservoir survey (Project 624). The core samples had been collected, extruded, and sectioned into various lengths by NEIC field personnel. Each section was wrapped in aluminum foil, labeled, and stored in a locked freezer until extracted for analysis. A total of 83 separated core fractions were then analyzed for total DDT compounds, polybrominated biphenyls, and hexabromobenzene. Empty aluminum and galvanized steel core sampling tubes were also received with the samples to be analyzed as field blanks.

## METHODOLOGY

The core samples were placed in a fumehood in aluminum foil dishes to thaw overnight. Any excess water in the sample dish was discarded and the sample mixed with a clean spatula. Approximately 10 grams of each sample were weighed into a pre-weighed dish and placed in a fumehood to air-dry. After several days, the sample and dish were re-weighed to determine the % of moisture in each sample.

Except as noted below, approximately 2 grams of each sample (non-dried) were weighed into clean glass vials (VOA bottles) fitted with screw caps and Teflon-liners. Two grams of anhydrous  $\text{Na}_2\text{SO}_4$  were also added to each vial and the samples were extracted by sonification with 10 mLs of a 50% acetone/hexane solvent mixture. The solvent was decanted off and the extraction repeated with a fresh 10 mL portion of solvent. The sonification was carried out for 2 minutes using an intermediate-size probe with a power level setting of 100 watts. The solvent extracts from each sample were combined and passed thru a funnel containing anhydrous  $\text{Na}_2\text{SO}_4$  which had been pre-washed with hexane. The extracts were concentrated to 10 mL using a nitrogen blowdown apparatus.

All samples were screened for compounds of interest by packed column electron-capture gas chromatography. Based on the screening results, high-level samples were simply diluted, whereas low-level samples were cleaned up by column chromatography. All samples requiring dilutions were diluted to the appropriate levels with hexane. All samples that did not require a dilution were cleaned up using Florisil column chromatography. The sample extract was placed on the head of a glass column packed with 20 grams of activated Florisil and eluted with 200 mls of 6% ethyl ether in hexane. The fraction was concentrated to less than 25 mls using a Kuderna-Danish evaporation apparatus and further concentrated to an appropriate volume using a nitrogen blowdown apparatus.

All sample extracts were analyzed by fused silica capillary column electron-capture gas chromatography using a 15 meter DB-5 column and a 25 meter OV-101 column. All extracts were analyzed for (1) Total DDT's, which included o,p'-DDE, p,p'-DDE, o,p'-DDD, p,p'-DDD, o,p'-DDT, p,p'-DDT; (2) hexabromobenzene (HBB); and (3) polybrominated biphenyls (PBB).

Several of the sample extracts were also analyzed for these compounds by gas chromatography/mass-spectroscopy (GC/MS).

NOTE: The following samples were extracted in the same manner as described above with the exception that a 10g sample size was weighed-out with 5 g of anhydrous  $\text{Na}_2\text{SO}_4$  and extracted with 20 mls of 50% acetone in hexane for the first extraction: 09-1, 09-2, 09-3, 11-1, 11-2, 13-1, 13-2, 13-3, 16-1, 16-2, 16-3, 18-1, 18-2, 18-3, 18-1 Dup., 18-2 Dup., and 18-3 Dup.

## RESULTS

The results of analysis by fused silica capillary column electron capture gas chromatography are given in Table 1. All results were calculated on a dry weight basis. Also listed in this table are the results for the percent moisture determinations for each core section. The results of analysis by GC/MS for several selective samples are listed in Table 2. A list of the gas chromatographic conditions are provided in Table 3.



QUALITY CONTROL

Four core samples were analyzed in duplicate and are designated as laboratory duplicates to differentiate them from the field duplicates collected by the field personnel. The results of these duplicate analyses are given in Table 4. The large, i.e., >40% relative percent difference (RPD) observed for several parameters in several samples is not unexpected for non-uniform samples of this sort.

Five solvent blanks were also analyzed along with the samples. These served as laboratory blanks and exhibited no significant interferences. Two field blanks were submitted for analysis consisting of one 3-foot unused galvanized steel core tube and one 3-foot unused aluminum core tube. The inside of the tubes were rinsed with 100 mLs of 50% acetone in hexane and concentrated to a final volume of 10 mLs. The aluminum tube blank exhibited no significant interferences while the galvanized steel tube blank showed trace levels of several of the DDT analogs along with a multitude of other unidentified electron capturing compounds. These trace level interferences did not affect results, however. The results of the blank analyses are also listed in Table 4.

Several core samples were spiked with the various compounds of interest and analyzed in the same manner as the samples. These results are listed in Table 5. The recoveries are considered very good considering the potential non-homogeneity of sediment samples.

Table 1  
RESULTS

Sample #	% Moisture	Concentrations (µg/g) <sup>1</sup>						Total DDT and Analogues	HBB	PBB
		DDE		DDD		DDT				
		o,p'	p,p'	o,p'	p,p'	o,p'	p,p'			
01-1	64.3	ND <sup>2,6</sup>	0.07	0.08	0.10	ND <sup>3</sup>	0.18	0.43	3.2	2.8
01-2	63.9	ND <sup>6</sup>	0.10	0.12	0.13	ND <sup>3</sup>	ND	0.35	0.42	0.46
02-1	55.4	ND <sup>3</sup>	0.31	0.22	0.58	0.10	3.8	5.0	1.0	1.0
02-2	48.2	0.06	0.48	0.22	0.58	0.36	5.3	7.0	1.1	0.76
03-1	64.9	ND <sup>3</sup>	0.32	0.22	0.57	ND <sup>3</sup>	0.61	1.7	0.96	0.84
03-2	61.1	ND <sup>4</sup>	1.1	4.2	12	ND <sup>5</sup>	1.2	18	ND <sup>7</sup>	ND <sup>7</sup>
03-3	51.8	0.12	1.0	4.8	12	0.49	6.4	25	ND <sup>4</sup>	ND <sup>4</sup>
04-1	34.8	0.27	2.2	12	20	32	200	270	15	330
04-2	45.2	ND <sup>4</sup>	7.2	32	32	4.8	47	120	90	23
05-1	63.2	0.06	0.48	0.64	1.5	0.11	11	14	92	0.94
05-2	65.3	1.2	2.8	4.2	8.8	0.22	7.2	24	6.2	ND <sup>5</sup>
05-3	68.1	2.2	5.3	22	58	110	790	990	ND <sup>5</sup>	ND <sup>5</sup>
05-4	61.6	ND <sup>6</sup>	ND <sup>6</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	-	ND <sup>5</sup>	ND <sup>5</sup>
06-1	57.1	ND <sup>3</sup>	0.18	0.32	1.1	0.19	0.84	2.6	12	2.2
06-2	43.7	0.08	0.34	0.62	0.66	0.21	1.6	3.5	28	0.56
06-3	60.5	0.24	0.68	2.1	2.6	ND <sup>4</sup>	2.2	7.8	0.92	ND <sup>5</sup>
06-4	51.9	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>4</sup>	ND <sup>4</sup>	ND <sup>4</sup>	ND <sup>4</sup>	-	ND <sup>5</sup>	ND <sup>5</sup>
07-1	72.0	0.31	1.8	9.7	24	4.6	64	100	ND <sup>5</sup>	14
07-2	71.5	3.8	9.7	7.0	220	ND <sup>8</sup>	74	380	9300	64
07-3	61.3	130	160	3400	3700	7300	11000	26000	100	ND <sup>9</sup>
07-4	63.4	0.06	0.05	0.68	0.85	1.1	2.0	4.7	1.0	ND <sup>5</sup>
08-1	70.3	ND <sup>3</sup>	2.1	6.0	17	ND <sup>10</sup>	11	36	2600	58
08-2	70.8	ND <sup>3</sup>	22	700	1100	140	890	2900	1800	ND <sup>5</sup>
08-3	63.2	21	47	2000	2200	1400	3200	8800	ND <sup>5</sup>	ND <sup>5</sup>
09-1	65.6	0.12	0.64	2.3	6.5	1.6	22	33	140	18
09-2	68.3	ND <sup>3</sup>	4.5	180	260	32	130	600	24	18
09-3	59.6	ND <sup>3</sup>	ND <sup>3</sup>	27	26	6.5	18	78	ND <sup>5</sup>	ND <sup>5</sup>
09-4	62.4	ND <sup>3</sup>	ND <sup>3</sup>	2.5	1.6	0.39	1.0	5.5	ND <sup>5</sup>	ND <sup>5</sup>

Table 1 (Cont'd)

Sample #	% Moisture	Concentrations (µg/g) <sup>1</sup>						Total DDT and Analogues	HBB	PBB
		DDE		DDD		DDT				
		o,p'	p,p'	o,p'	p,p'	o,p'	p,p'			
10-1	0.9	ND <sup>3</sup>	0.17	0.60	1.5	0.48	3.0	5.8	55	14
10-2	64.1	ND <sup>10</sup>	ND <sup>10</sup>	275	175	ND <sup>8</sup>	ND <sup>8</sup>	450	440	66
10-3	56.3	ND <sup>10</sup>	ND <sup>10</sup>	4.0	3.8	ND <sup>8</sup>	ND <sup>8</sup>	7.8	14	ND <sup>8</sup>
11-1	68.5	0.13	0.61	4.0	7.0	0.47	4.9	17	97	4.8
11-2	65.6	0.28	0.74	8.0	12	3.6	8.3	33	610	21
12-1	68.7	0.10	0.39	2.9	6.4	1.1	3.9	15	90	5.0
12-2	63.5	0.19	0.25	4.8	6.2	2.0	3.0	16	170	8.0
12-3	55.9	ND <sup>6</sup>	ND <sup>6</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	-	ND <sup>5</sup>	ND <sup>5</sup>
13-1	67.1	0.07	0.31	2.0	4.7	2.8	5.0	15	44	4.2
13-2	67.7	0.15	0.74	3.8	9.2	ND <sup>5</sup>	2.0	16	500	25
13-3	67.4	ND <sup>3</sup>	ND <sup>3</sup>	46	62	30	86	220	28	1.0
13-4	62.2	40	32	1500	1400	700	1100	4800	ND <sup>8</sup>	ND <sup>8</sup>
13-5	55.2	0.12	0.06	3.4	4.4	0.40	1.1	9.5	ND <sup>5</sup>	ND <sup>5</sup>
14-1	66.5	9.3	23	740	1300	140	1800	4000	5.7	2.7
14-2	13.5	0.12	0.28	7.0	13	0.80	10	31	ND <sup>5</sup>	ND <sup>5</sup>
14-3	15.1	ND <sup>6</sup>	ND <sup>6</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	-	ND <sup>4</sup>	ND <sup>4</sup>
15-1	71.9	0.12	0.44	4.1	7.8	0.74	7.6	21	80	4.0
15-2	68.9	0.32	1.0	5.7	12	ND <sup>4</sup>	1.6	21	660	16
15-3	67.1	90	66	1500	1400	1100	1200	5400	54	ND <sup>10</sup>
15-4	58.8	35	37	1200	1500	530	1000	4300	44	ND <sup>9</sup>
15-5	56.3	ND <sup>3</sup>	ND <sup>3</sup>	0.20	0.29	ND <sup>4</sup>	ND <sup>4</sup>	0.49	ND <sup>5</sup>	ND <sup>5</sup>
16-1	64.1	ND <sup>3</sup>	0.41	2.5	12	3.0	20	38	86	12
16-2	64.5	0.14	0.55	1.4	3.4	13	12	30	220	6.5
16-3	67.1	0.66	0.80	18	20	2.4	12	54	ND <sup>5</sup>	ND <sup>5</sup>
16-4	55.0	0.18	0.16	4.8	5.0	ND <sup>4</sup>	0.48	11	ND <sup>5</sup>	ND <sup>5</sup>
17-1	64.2	0.06	0.27	2.0	5.2	1.2	14	23	52	5.3
17-2	68.0	0.22	0.82	1.1	1.8	ND <sup>4</sup>	1.8	5.7	120	1.6
17-3	63.7	3.4	4.6	90	120	10	30	260	1.9	ND <sup>5</sup>
17-4	57.3	ND <sup>6</sup>	ND <sup>6</sup>	0.12	0.21	ND <sup>3</sup>	ND <sup>3</sup>	0.33	ND <sup>4</sup>	ND <sup>4</sup>
17-5	36.8	ND <sup>6</sup>	ND <sup>6</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	-	ND <sup>4</sup>	ND <sup>3</sup>

Table 1 (Cont'd)

Sample #	% Moisture	Concentrations (µg/g) <sup>1</sup>						Total DDT and Analogues	HBB	PBB
		DDE		DDD		DDT				
		o,p'	p,p'	o,p'	p,p'	o,p'	p,p'			
18-1	64.0	0.10	0.29	4.5	6.2	1.8	7.8	21	4.3	1.2
18-2	31.3	ND <sup>3</sup>	ND <sup>3</sup>	0.12	0.24	ND <sup>4</sup>	ND <sup>4</sup>	0.36	0.58	ND <sup>5</sup>
18-3	61.6	1.0	1.4	48	50	1.2	19	120	ND <sup>5</sup>	ND <sup>5</sup>
18-1 Dup.	66.3	0.10	0.27	3.4	5.6	0.81	4.0	14	5.0	1.3
18-2 Dup.	30.2	ND <sup>3</sup>	ND <sup>3</sup>	0.16	0.51	ND <sup>4</sup>	3.2	3.9	0.81	6.8
18-3 Dup.	56.9	0.56	1.1	28	34	14	64	140	ND <sup>5</sup>	ND <sup>5</sup>
19-1	56.5	0.08	0.28	2.3	5.0	0.21	3.4	11	34	3.0
19-2	70.5	1.0	1.6	40	35	ND <sup>10</sup>	10	88	42	4.8
19-3	34.8	ND <sup>6</sup>	ND <sup>6</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	-	ND <sup>4</sup>	ND <sup>4</sup>
20-1	61.8	0.11	0.38	1.7	3.9	0.18	6.7	1.3	82	3.4
20-2	68.6	4.0	6.0	170	160	12	210	560	28	ND <sup>5</sup>
20-3	18.4	ND <sup>3</sup>	ND <sup>3</sup>	0.50	04.6	ND <sup>4</sup>	0.10	1.1	ND <sup>5</sup>	ND <sup>5</sup>
21-1	66.6	0.06	0.26	2.0	4.2	0.16	2.7	9.4	54	3.4
21-2	69.4	2.6	3.0	88	84	3.1	18	200	32	ND <sup>7</sup>
21-3	51.9	ND <sup>6</sup>	ND <sup>6</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	-	ND <sup>4</sup>	ND <sup>4</sup>
21-1 Dup.	67.9	0.06	0.26	2.0	4.2	0.20	2.3	9.0	52	3.3
21-2 Dup.	70.0	2.2	2.6	78	70	ND <sup>7</sup>	2.3	160	39	ND <sup>7</sup>
22-1	70.3	0.06	0.32	2.3	4.8	ND <sup>4</sup>	1.1	8.6	35	2.1
22-2	72.3	4.5	5.2	180	170	ND <sup>7</sup>	7.0	370	48	5.2
22-3	64.9	0.19	0.30	5.1	9.6	ND <sup>4</sup>	0.74	16	ND <sup>5</sup>	ND <sup>5</sup>
23-1	66.6	0.08	0.36	1.6	3.4	0.22	2.0	7.7	180	4.4
23-2	67.6	0.70	1.8	13	32	1.0	38	87	22	ND <sup>5</sup>
23-3	67.1	3.8	4.0	150	140	ND <sup>5</sup>	9.7	310	ND <sup>7</sup>	ND <sup>7</sup>
23-4	46.6	ND <sup>6</sup>	ND <sup>6</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	ND <sup>3</sup>	-	ND <sup>4</sup>	ND <sup>4</sup>

- (1) Concentration calculated on a dry weight basis
- (2) ND = none detected
- (3) Limit of detection = 0.05  $\mu\text{g/g}$
- (4) Limit of detection = 0.10  $\mu\text{g/g}$
- (5) Limit of detection = 0.50  $\mu\text{g/g}$
- (6) Limit of detection = 0.02  $\mu\text{g/g}$
- (7) Limit of detection = 1.0  $\mu\text{g/g}$
- (8) Limit of detection = 5.0  $\mu\text{g/g}$
- (9) Limit of detection = 25  $\mu\text{g/g}$
- (10) Limit of detection = 2.0  $\mu\text{g/g}$

Table 3  
GAS CHROMATOGRAPHIC CONDITIONS

	Column, Fused Silica	
	DB-5	OV-101
Length	15 Meters	25 Meters
Coating Thickness	1.0 $\mu\text{m}$	0.25 $\mu\text{m}$
Initial Temp., $^{\circ}\text{C}$	60	60
Initial Time, min.	0.50	0.50
Program Rate, $^{\circ}\text{C}/\text{min.}$	10	10
Final Temp. 1, $^{\circ}\text{C}$	215	190
Final Temp. 1 Time, min.	25	25
Program Rate, $^{\circ}\text{C}/\text{min.}$	10	10
Final Temp. 2, $^{\circ}\text{C}$	270	270
Final Temp. 2 Time, min.	30	30
Injection Temp., $^{\circ}\text{C}$	230	230
Detector Temp., $^{\circ}\text{C}$	280	280
Septum Sweep, $\text{mL}/\text{min.}$	2	2
Carrier/Make-up Flow, He	30	30
Inlet Purge, $\text{mL}/\text{min.}$	40	40
Linear Velocity, $\mu$	24	26
Injection Volume, $\mu\text{l}$	1.0	1.0
Detector, EC	D	C

Table 2  
GC/MS CONFIRMATION RESULTS

Compound	Detection Limit	Concentration ( $\mu\text{g/g}$ ) <sup>1</sup>				
		#05-3	#08-1	#08-2	#08-3	#15-4
o,p'-DDE	10	ND <sup>2</sup>	ND	ND	22	19
p,p'-DDE	20	ND	ND	ND	38	25
o,p'-DDD	50	ND	ND	680	1900	820
p,p'-DDD	50	ND	ND	1100	2200	970
o,p'-DDT	50	93	ND	170	1300	210
p,p'-DDT	50	720	ND	780	3600	480
Hexabromobenzene	100	ND	2500	1800	ND	ND
Polybrominated Biphenyl	600	ND	ND	ND	ND	ND

(1) dry weight basis

(2) ND = none detected

Table 4  
QUALITY CONTROL SUMMARY

	#07-3			#08-3			#12-1			#16-3		
	1	2	RPD <sup>1</sup>	1	2	RPD <sup>1</sup>	1	2	RPD <sup>1</sup>	1	2	RPD <sup>1</sup>
<u>Duplicate Analyses</u>												
o,p'-DDE	130	120	8	21	25	9	0.10	0.08	22	0.66	0.74	11
p,p'-DDE	160	160	0	47	59	23	0.39	0.48	21	0.80	0.84	5
o,p'-DDD	3400	3700	8	2000	2400	18	2.9	3.0	3	18	22	10
p,p'-DDD	3700	5000	30	2200	2600	17	6.4	7.2	12	20	24	18
o,p'-DDT	7300	8600	16	1400	2200	44	1.1	0.70	44	2.4	2.6	8
p,p'-DDT	11000	12000	9	3200	4600	36	3.9	6.4	48	12	14	15
HBB	100	100	0	ND	ND	-	90	78	14	ND	ND	-
PBB	ND <sup>2</sup>	ND	-	ND	ND	-	5.0	4.0	22	ND	ND	-

(1) RPD = Relative Percent Difference

(2) ND = none detected



Table 4 (Cont'd)  
QUALITY CONTROL SUMMARY

Sample	Concentration ( $\mu\text{g/g}$ )							
	DDE		DDD		DDT		HBB	PBB
	o,p'	p,p'	o,p'	p,p'	o,p'	p,p'		
<u>Blank Analyses</u>								
Blank 1	ND	ND	ND	ND	ND	ND	ND	ND
Blank 2	ND	ND	ND	ND	ND	ND	ND	ND
Blank 3	ND	ND	ND	ND	ND	ND	ND	ND
Blank 4	ND	ND	ND	ND	ND	ND	ND	ND
Blank 5	ND	ND	ND	ND	ND	ND	ND	ND
Aluminum Pipe Blank	ND	ND	ND	ND	ND	ND	ND	ND
Galvanized Steel Blank	ND	ND	<0.20	<0.20	<0.20	<0.20	ND	ND
Limit of Detection	0.10	0.10	0.10	0.10	0.10	0.10	0.20	0.20

(1) Assumed a 2 g sample size for calculation purposes

Table 5  
SPIKE RECOVERIES

Compound	Amount Added (µg)	% Recovery			
		#10-1	#17-2	#18-2	#20-3
o,p'-DDE	2.5	84	104	95	84
p,p'-DDE	2.5	96	108	97	84
o,p'-DDD	2.5	76	108	99	84
p,p'-DDD	2.5	60	100	100	87
o,p'-DDT	2.5	80	104	92	75
p,p'-DDT	2.5	NA <sup>1</sup>	108	94	71
HBB	2.5	NA	160	118	87
PBB	2.5	NA	180	104	90

(1) NA = not applicable



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY, REGION V

230 South Dearborn Street

CHICAGO IL 60604

## FACSIMILE REQUEST AND COVER SHEET

PLEASE PRINT IN BLACK INK ONLY

TO

ANNE COUTURE

OFFICE/PHONE

517-373-4797

MACHINE NR:

517-373-4797

VERIFICATION NR:

~~517-373-4797~~ 373 8449

REGION/LAB

MDNR

FROM

P. MILLER

PHONE

312 886 4783

MAIL CODE

SHE-12

OFFICE

EPA WMD

DATE

9-26-86

NUMBER OF PAGES TO INCLUDE THIS COVER SHEET

29

Please number all pages

## INFORMATION FOR SENDING FACSIMILE MESSAGES

EQUIPMENT

FACSIMILE  
NUMBERVERIFICATION  
NUMBER

PANAFAX PX-100

FTS: 886-9096(auto)

Comm: (312)886-9096

FTS: 886-3096

Comm: (312)886-3096

XEROX 400

FTS: 886-3096(manual)

Comm: (312)886-3096

FTS: 886-3096

Comm: (312)886-3096

PAGE 0 OF 29 PAGES