

Stan A. Huber Consultants, Inc.

Health Physics and Radiation Safety Services

200 North Cedar Road - New Lenox, Illinois 60451-1751 - (800) 383-0468 or (815) 485-6161 - FAX (815) 485-4433 - Email sahci@sahci.com - Home Page www.sahci.com

November 8, 2021

Angel Camacho SET Environmental 450 Sumac Road Wheeling, Illinois 60090

RE: Thorium Monitoring – City of Chicago Department of Water Management

CDOT Permit: 1610002-233 E. Erie St.

Dear Mr. Camacho:

Stan A. Huber Consultants, Inc (SAHCI) was hired by your firm to provide radiation monitoring during the excavation for replacement of a Chicago Department of Water Management valve at 233 E. Erie St. in Chicago, Illinois. The monitoring was performed by Glenn Huber, SAHCI Health Physicist, on November 4, 2021. All activities were conducted under the guidance of document *SET General Procedure for Thorium Monitoring*.

<u>Instrumentation</u>

Surface gamma scans were performed using a Ludlum Model 2221 Scaler / Ratemeter (serial no. 126497) with attached Ludlum Model 44-10 2"x2" Nal Detector (w/ 6" collimated lead shield). The instrument was calibrated on May 5, 2021. The US Environmental Protection Agency (USEPA) action level of 7.1 picocuries per gram (pCi/g) total thorium for this instrument is 6,383 counts per minute (cpm).

The average background count rate for these locations was measured at 1,864 cpm.

Soil Gamma Scans

Gamma surface scans were performed using the Ludlum Model 2221 Scaler / Ratemeter described above. Survey data was collected by entering the excavation and recording the highest count rate for the floor and walls to a depth of 42 inches below ground surface. Material excavated below 42 inches, to a maximum depth of 96 inches, was monitored in the excavator bucket as it was removed. All asphalt, concrete, and soil were loaded directly into a truck for disposal.

The maximum gamma count rate for each lift was recorded on the attached Radiation Survey Form. The count rates in the excavations ranged from 1,900 cpm to 3,400 cpm. No count rates were found at any time that exceeded the threshold limit of 6,383 cpm.

Additional Monitoring

Since no count rates were identified above the 7.1 pCi/gram threshold limit, no additional soil sampling, air monitoring, or personnel monitoring were performed.

I will be providing a copy of this report to both the City of Chicago Department of Public Health and US Environmental Protection Agency, as required.

Thank you for your assistance with this project. If you have any questions or need additional information, please call me at (815) 485-6161.

Sincerely, Stan A. Huber Consultants, Inc.

Glenn Huber, CHP President

| Page | / of | - 1 |
|------|-------------|-----|
| | | |



Radiation Survey Form

Location/ Project ID: DWm - 233 B. EALE St. - VAWE REPLACEMENT ROW RADIOGICAL SOIL

SURVEY

Date: 11/4/221 Technician: BRIAN Scyming Serial No. : 126497 Inst Model: LVDLUM - 222 | Lift Elevation: __O -96" Probe Type: 1"x1" Nal / 2"x2" Na Shielded / Not Shielded Background 1864 Action Level: cpm Write grid designations in circles. Record highest counts for grid in cpm. Record 30 second counts at grid intersections (if required). Shade areas of elevated counts and record max cpm. N scale SIDEYALK BUILDING FOOTPRINT 1900 2600 3100 3400 2600 3400