06/03/2014 10:11

06/03/2014 10:14

30SS895-55

ORTH-LAM RESIN

FOR USE BY TRAINED PERSONNEL ONLY. USE WITH ADEQUATE VENTILATION. NO SMOKING.
RESIN SOLUTION UN 1866 : CONTAINS STYRENE MONOMER

HAZARD **WARNING** **FLAMMABLE LIQUID**

POSSIBLE CANCER HAZARD BASED ON TESTS WITH LABORATORY ANIMALS
Hazardous polymerization may occur at prolonged storage above 100°F. May be toxic if absorbed throught the skin.

EFFECTS OF OVEREXPOSURE

Inhalation--May cause drowsiness, nausea, headache, dizziness, narcosis, loss of coordination, cyanosis and irritation of upper respiratory tract. Severe exposure may cause a confused state.
Skin contact--May cause irritation, pain, redness, and tearing.
Ingestion--May cause sore throat, abdominal pain, vommiting, and nausea.

EMERGENCY FIRST AID

Inhalation--Remove from exposure. If breathing has stopped or is difficult, administer artificial respiration or oxygen as indicated. Seek immediate medical attention.
Skin contact--Remove contaminated clothing. Wash skin thoroughly with soap and water.
Flush area for at least ten minutes. If irritation occurs seek medical aid.
Ingestion--This material is an aspiration hazard. DO NOT induce vomiting in unconcious victim. Seek medical aid.

PROTECTIVE APPAREL

Wear NIOSH/MSHA approved respirator for protection against organic vapors. Wear chemical resistant gloves and garments to prevent prolonged contact.

FIRE FIGHTING MEDIA

Carbon Dioxide, dry chemical, foam and water fog.

STORAGE AND TRANSFER

Flammable! Do not store in direct sunlight or at temperature greater than 100°F. Store away from heat and sparks. Flammable vapors may travel to distant ignition sources. Container(s) should be grounded and bonded during material transfers to prevent static sparks. Avoid storage longer than 3 months.

SPILL/LEAK INSTRUCTIONS

Remove all sources of ignition. Dike large spills to prevent entry into sewers or storm drains. Soak up with inorganic absorbant and place in labeled container.

TARGET ORGAN INFORMATION

Overexposure to components of this material may cause damage to or worsen preexisting conditions of the kidney, hearing, respiratory tract, testis, liver, or central nervous system.

PRIMARY ROUTES OF ENTRY

Inhalation, Skin absorption, Skin contact, Eye contact.
CONSULT MATERIAL SAFETY DATA SHEET FOR ADDITIONAL INFORMATION

REVCHEM PLASTICS, INC.

2720 SOUTH WILLOW AVE. :BLOOMINGTON,
WWW.REVCHEM.COM : (909) 877-8477 : FAX (909) 877-8475

HEALTH
FLAMMA
REACTIV

POLYESTER

30SS895-55

ORTH LAM RESIN

LOT-3712H6 WEIGHT 500LBS.
DATE :09/19/06

OUT OF REACH OF CHILDREN. DO NOT CUT OR WELD ON OR NEAR TY CONTAINER.

FLAMMABLE LIQUID

3

RESIN SOLUTION, UN 1866

RTE 145

WARNING !!! This product contains chemicals that are considered by the state of California to cause cancer or Birth Defects. Please use caution when handling.

Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to the contents and suitability. Nothing herein shall constitute a warranty, express or implied, including any warranty of merchantability or fitness, not is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our material and in no event shall we be liable for special, incidental, or consequential damages.