

---

# **USEPA Superfund Program Landfill Methane-to-Energy Pilot**

**S. Steven Chang**

**(chang.steven@epa.gov)**

**US Environmental Protection Agency**

**Office of Superfund Remediation and Technology Innovation**

**May 6, 2010**

# Pilot Goal:

---

- ◆ Evaluate and increase the number of landfills on the Superfund National Priorities List (NPL) that use the methane generated on-site.

# Technical Considerations for Using Landfill Gas:

---

## ◆ Quality of Landfill Gas (LFG)

- » Are there any known compounds in the gas or landfill that would preclude or greatly impact the cost of using LFG? (i.e. radioactive, infectious, explosive, or ordnance waste).

## ◆ Quantity of LFG

- » How much gas is present?
- » What is the methane concentration?
- » How fast is the flow rate declining?

# Technical Considerations for Using Landfill Gas (concluded):

---

## ◆ Accessibility of LFG

- » How expensive will it be to collect the gas?
- » Is a gas collection system already in place?
- » Are there complicating site factors such as flooded wells, very shallow waste, unexploded ordnances, or unmapped trench-and-fill cells?

## ◆ Energy demand

- » What is the energy need for landfill related activities (e.g., ground water pump and treat system)?
- » What remediation equipment is used on site?
- » Is the landfill located in an area with nearby off-site energy demands that could be met by landfill methane-to-energy projects?

# Initial Observations:

---

- ◆ Many NPL landfills in EPA Region 1, 2, and 3 in the Northeast have received so little municipal solid wastes in the last 20 years that they are producing very little recoverable methane.
- ◆ Few NPL landfills are producing marketable quantities of methane, but might produce enough to off-set on-site electricity usage.
- ◆ The cost for recovery of small methane flows from NPL landfills is expensive, and could benefit greatly from an existing well or vent field.
- ◆ Energy demands at NPL landfills are generally in the size range of microturbines.

# Developing Screening Criteria:

---

- ◆ The ERG-Shaw-Cornerstone team is developing draft screening criteria that can be used in conjunction with the EPA *LandGEM* and *LFGcost* models to determine the practicality of using landfill methane to produce energy for on-site use.
- ◆ These criteria will include factors that are likely to have a significant positive or negative impact on gas recovery potential.

# Schedule:

---

- ◆ Draft Screening Tool - July 2010
- ◆ Final Screening Tool - August 2010
- ◆ EPA final report – by December 2010

# Next Steps:

---

- ◆ Encourage EPA Regions to find suitable NPL landfill methane-to-energy projects using the screening criteria
- ◆ Encourage EPA Regions to collaborate with interested municipal authorities and Responsible Parties to implement projects